



## Submittal Data Sheet

0.75 Ton One Way Blow Cassette

FXEQ09PVJU

### FEATURES

- Compact design with 7-7/8" body height and 3-3/16" panel height
- Outside air integration ready (requires field supplied accessories)
- Energy efficient fan with 5 speed settings
- Mold resistant resin decoration panel that matches standard ceiling color

### BENEFITS

- Increased overall heating effect due to the innovative discharge air louver design
- Compact heat exchanged and fan design to increase space saving





**Submittal Data Sheet**  
0.75 Ton One Way Blow Cassette  
FXEQ09PVJU

**PERFORMANCE**

Indoor Unit Model No.	FXEQ09PVJU	Indoor Unit Name:	0.75 Ton One Way Blow Cassette
Type:	Ceiling Cassette	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	9,500	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):		Rated Piping Length(ft):	
Cooling Input Power (kW):		Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	10,500		

**INDOOR UNIT DETAILS**

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (HH/H/M/L/SL) (CFM):	244/226/205/187/170
Power Supply Connections:		Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.40	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15.00	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	7-7/8 x 33-1/16 x 18-1/2	Condensate Connection (inch):	1-1/32
Panel (HxWxD) (in):	3-3/16 x 37-13/32 x 21-5/8	Sound Pressure (H/M/L/SL) (dBA):	31/30/29/28
Net Weight (lb):	38	Sound Power Level (dBA):	
Panel Weight (lb):	18	Ext. Static Pressure (Rated/Max) (inWg):	/

**Submittal Data Sheet**  
**0.75 Ton One Way Blow Cassette**  
**FXEQ09PVJU**

**DIMENSIONAL DRAWING**

