



## Submittal Data Sheet

12-Ton VRV-IV Heat Pump Unit - 230V

RXYQ144TTJU

### FEATURES

- Variable Refrigerant Temperature (VRT) control allows the VRV IV to deliver up to 28% of improvement in seasonal cooling efficiency compared to previous Daikin VRV heat pump systems
- Same product structure for 230V and 460V simplifies ordering
- The rated seasonal cooling efficiency has been improved by an average of 11% compared to VRV III
- Improved efficiency with IEER values now up to 28
- Larger capacity single modules ranging up to 14 tons and systems up to 34 tons allow for a more flexible system design
- New configurator software designed to simplify the commissioning and maintenance of the system
- Larger capacity single modules allow for opportunity to reduce electrical connections, piping connections and outdoor unit mounting fixtures
- System wide auto-climate adjustment technology to increase the energy efficiency
- All inverter compressors to increase the efficiency and avoid starting current inrush
- Assembled in the US to increase flexibility and reduce lead times
- Standard Limited Warranty: 10-year warranty on compressor and all parts

### BENEFITS

- 3 row 7mm heat exchanger coil improves efficiency
- Inverter control board cooled by refrigerant to avoid influence from ambient temperatures
- Heat exchanger coil wraps around on all 4 sides of the unit to increase the surface area / efficiency
- Designed with reduced MOP to optimize installation cost
- Digital display on the unit for improved and faster configuration, commissioning, and trouble shooting.





## Submittal Data Sheet

12-Ton VRV-IV Heat Pump Unit - 230V

RXYQ144TTJU

### PERFORMANCE

Outdoor Unit Model No.	RXYQ144TTJU	Outdoor Unit Name:	12-Ton VRV-IV Heat Pump Unit - 230V
Type:	Heat Pump	Unit Combination:	
Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Rated Piping Length(ft):			
Rated Height Difference (ft):	0.00		
Rated Cooling Capacity (Btu/hr):	138,000	Rated Heating Capacity (Btu/hr):	154,000
Nom Cooling Capacity (Btu/hr):		Nom Heating Capacity (Btu/hr):	
Cooling Input Power (kW):	11.80	Heating Input Power (kW):	11.10
EER (Non-Ducted/Ducted):	12.30 / 11.50	Heating COP (Non-Ducted/Ducted):	4.1 / 3.7
IEER (Non-Ducted/Ducted):	24.10 / 21.00	Heating COP 17F (Non-Ducted/Ducted):	2.3 / 2.2

### OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 3	Compressor Type	Inverter
Power Supply Connections:	L1, L2, L3 Ground	Capacity Control Range (%):	20 - 100
Min. Circuit Amps MCA (A):	55.1	Capacity Index Limit:	72.0 - 187.0
Max Overcurrent Protection (MOP) (A):	60	Airflow Rate (H) (CFM):	8,228
Max Starting Current MSC(A):		Gas Pipe Connection (inch):	1-1/8
Rated Load Amps RLA(A):	16.7+16.7	Liquid Pipe Connection (inch):	1/2
Dimensions (Height) (in):	66-11/16	H/L Pressure Connection (inch)	
Dimensions (Width) (in):	48-7/8	H/L Equalizing Connection (inch)	
Dimensions (Depth) (in):	30-3/16	Sound Pressure (H) (dBA):	64
Net Weight (lb):	695	Sound Power Level (dBA):	
		Max. No. of Indoor Units:	25

**Submittal Data Sheet**  
 12-Ton VRV-IV Heat Pump Unit - 230V  
 RXYQ144TTJU

**SYSTEM DETAILS**

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	23 - 122
Holding Refrigerant Charge (lbs):	18.1	Heating Operation Range (°F WB):	-4 - 60
Additional Charge (lb/ft):		Max. Pipe Length (Vertical) (ft):	295
Pre-charge Piping (Length) (ft):		Cooling Range w/Baffle (°F DB):	-
Max. Pipe Length (Total) (ft):	540	Heating Range w/Baffle (°F WB):	-
Max Height Separation (Ind to Ind ft):	0		

**DIMENSIONAL DRAWING**

