

Submittal Data Sheet

1.0-Ton Wall Mounted Unit FXAQ12PVJU

FEATURES

- Auto-swing mechanism ensures efficient air distribution via louvers that automatically close when the unit is turned off
- Easy to clean front panel with a flat smooth surface that can be removed for additional cleaning
- Five different airflow distribution angles programmable by the optional controller
- Condensate drain pipe can be installed on either the left or right side of the unit.
- Wide air discharge outlet distributes a comfortable airflow throughout the entire space
- Standard Limited Warranty: 10-year warranty on compressor and all parts







Submittal Data Sheet

1.0-Ton Wall Mounted Unit FXAQ12PVJU

PERFORMANCE			
Indoor Unit Model No.	FXAQ12PVJU	Indoor Unit Name:	1.0-Ton Wall Mounted Unit
Туре:	Wall Mounted	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	12,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	8,900	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.030	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	13,500		
Heating Input Power (kW):	0.04		

INDOOR UNIT DETAILS				
Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/L) (CFM):	290/180	
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):		
Min. Circuit Amps MCA (A):	0.40	Gas Pipe Connection (inch):	1/2	
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4	
Dimensions (HxWxD) (in):	11-3/8 x 31-1/4 x 9-1/4	Condensate Connection (inch):	11/16	
Panel (HxWxD) (in):		Sound Pressure (H/L) (dBA):	38/31	
Net Weight (lb):	26	Sound Power Level (dBA):		
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	0.00 / 0.00	



Submittal Data Sheet

1.0-Ton Wall Mounted Unit FXAQ12PVJU

DIMENSIONAL DRAWING

