



Submittal Data Sheet

1.0-Ton Slim Duct Built-in Concealed Ceiling Unit

FXDQ12MVJU

FEATURES

- The slim height, at only 7-7/8", makes it suitable for most of the applications where attic / bulkhead space is limited
- With a sound level as low as 29dBA, these systems are among the quietest on the market
- Washable filter included
- Built-in condensate pump
- Blends unobtrusively with any interior decor; only the suction and discharge grills are visible
- Standard Limited Warranty: 10-year warranty on compressor and all parts





Submittal Data Sheet

1.0-Ton Slim Duct Built-in Concealed Ceiling Unit

FXDQ12MVJU

PERFORMANCE

Indoor Unit Model No.	FXDQ12MVJU	Indoor Unit Name:	1.0-Ton Slim Duct Built-in Concealed Ceiling Unit
Type:	Ducted	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	12,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	8,800	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.100	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	13,500		
Heating Input Power (kW):	0.08		

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/L) (CFM):	280/226
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.90	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	7-7/8 x 27-9/16 x 24-7/16	Condensate Connection (inch):	1-1/32
Panel (HxWxD) (in):		Sound Pressure (H/L) (dBA):	33/29
Net Weight (lb):	51	Sound Power Level (dBA):	51
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	0.12 / 0.12

Submittal Data Sheet

1.0-Ton Slim Duct Built-in Concealed Ceiling Unit
FXDQ12MVJU

DIMENSIONAL DRAWING

FXD07/09/12MVJU
Unit (in.)

