



## Submittal Data Sheet

2.0-Ton 4-Way Blow Ceiling-Suspended

FXUQ24PVJU

### FEATURES

- Low profile of less than 8" with the option to be partially recessed in a false ceiling
- Built-in condensate pump with 19-1/2" lift and safety float switch
- Auto swing function ensures efficient air and temperature distribution
- Air can be discharged in five different angles between 0 and 60°
- Low sound pressure levels down to 36 dBA
- The optional Sensor Kit (occupancy and surface temperature) together with air temperature sensor and advanced control functions enables the unit to provide an exceptional comfort level, energy efficiency, and flexibility

### BENEFITS

- Great solution for projects with low or no false ceilings thanks to the compact design
- The four individually controlled air louvers in the unit enable comfortable space environment in a variety of different room layouts
- Low energy consumption thanks to a specially developed small tube heat exchanger, DC fan motor and drain pump





## Submittal Data Sheet

2.0-Ton 4-Way Blow Ceiling-Suspended

FXUQ24PVJU

### PERFORMANCE

Indoor Unit Model No.	FXUQ24PVJU	Indoor Unit Name:	2.0-Ton 4-Way Blow Ceiling-Suspended
Type:		Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	24,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):		Rated Piping Length(ft):	
Cooling Input Power (kW):		Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	27,000		

### INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	795/689/565
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.60	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15.00	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	7-13/16 x 37-3/8 x 37-3/8	Condensate Connection (inch):	
Panel (HxWxD) (in):		Sound Pressure (H/L) (dBA):	44/40
Net Weight (lb):	58	Sound Power Level (dBA):	
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	/

**Submittal Data Sheet**  
**2.0-Ton 4-Way Blow Ceiling-Suspended**  
**F XUQ24PVJU**

**DIMENSIONAL DRAWING**

