



## Submittal Data Sheet

1.5-Ton VISTA 2x2 Cassette Unit for VRV

FXZQ18TAVJU

### FEATURES

- Six capacity options, including a new 5,800 Btu/h model
- 4-way, 3-way, and 2-way blow configurability
- Independently motorized louver outlets
- High efficiency DC fan motor with Auto fan speed control
- Low profile decoration panel design measures a mere 5/16" below the ceiling
- Integral condensate pump with up to 24-13/16" (630mm) lift from the drain outlet
- Independently configurable auxiliary heat on/off temperatures
- Direct outside air integration possible
- Two decoration panel design colors available: BYFQ60C3W1W (white) or BYFQ60C3W1S (silver/white)
- Universal Design award winning design
- Standard Limited Warranty: 10-year limited parts warranty

### BENEFITS

- 24-7/16" x 24-7/16" decoration panel design simplifies ceiling coordination by eliminating overlap of adjacent ceiling tiles in a 2x2 ceiling grid
- Auto fan speed control can reduce operational energy input by intelligently adjusting the fan speed in response to room temperature
- Independently adjustable air flow louvers allow for a high degree of air distribution flexibility
- The optional space and presence sensor kit optimizes energy efficiency by automatically adjusting the set point temperature when no occupants are detected by the unit
- The optional space and presence sensor kit enhances occupant comfort by automatically adjusting the air flow louvers to avoid cold drafts and reduce stratification during heating operation



VRV





## Submittal Data Sheet

1.5-Ton VISTA 2x2 Cassette Unit for VRV

FXZQ18TAVJU

### PERFORMANCE

Indoor Unit Model No.	FXZQ18TAVJU	Indoor Unit Name:	1.5-Ton VISTA 2x2 Cassette Unit for VRV
Type:	Cassette	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	18,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	13,000	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.092	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	20,000		
Heating Input Power (kW):	0.09		

### INDOOR UNIT DETAILS


Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	511/441/353
Power Supply Connections:	L1, L2, G	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.6	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	10-1/4 x 22-5/8 x 22-5/8	Condensate Connection (inch):	25/32
Net Weight (lb):	40.8	Sound Pressure (H/M/L) (dBA):	43/40/33
Ext. Static Pressure (Rated/Max) (inWg):	N/A / N/A	Sound Power Level (dBA):	60

# Submittal Data Sheet

1.5-Ton VISTA 2x2 Cassette Unit for VRV

FXZQ18TAVJU

## DIMENSIONAL DRAWING



Daikin City Generated Submittal Data

Daikin North America LLC, 5151 San Felipe, Suite 500, Houston, TX, 77056

[www.daikinac.com](http://www.daikinac.com) [www.daikincomfort.com](http://www.daikincomfort.com)

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)